

SAFETY DATA SHEET

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 453/2010

1. SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1	Product identifier	
	Product Name	NEOASTRA DG – BULK.
	CAS No.	Mixture.
	EINECS No.	Mixture.
	REACH Registration No.	None assigned.
1.2	Relevant identified uses of the substance or mixture and uses advised against	
	Identified use(s)	For use in the Magnetic Particle Inspection Process (BS EN ISO 9934-2:2002).
	Uses advised against	None known.
1.3	Details of the supplier of the Safety Data	
	Sheet	
	Company Identification	Johnson and Allen Ltd
		Neocol Works
		Smithfield
		Sheffield
		S3 7AR.
	Telephone	0114 2738066.
	Fax	0114 2729842.
	E-Mail (competent person)	info@johnsonandallen.co.uk
1.4	Emergency telephone number	
	Emergency Phone No.	0114 2738066. (UK office hours 08.30-17.00).

2. SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture
- 2.1.1 Regulation (EC) No. 1272/2008 (CLP)
- 2.1.2 Directive 67/548/EEC & Directive 1999/45/EC
- 2.2 Label elements
- 2.2.1 Label elements Product Name Hazard Pictogram

Signal word(s) Hazard statement(s)

Precautionary statement(s)

Asp. Tox. 1; May be fatal if swallowed and enters airways. Repeated exposure may cause skin dryness or cracking. Xn; Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.

According to Regulation (EC) No. 1272/2008 (CLP) NEOASTRA DG – BULK.



GHS08 Danger. H304: May be fatal if swallowed and enters airways. EUH066: Repeated exposure may cause skin dryness or cracking. P301 + P310: IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician. P331: Do NOT induce vomiting. P405: Store locked up. P501: Dispose of contents/container to: Licensed recycler.



2.2.2 Label elements Hazard Symbol According to Directive 67/548/EEC & Directive 1999/45/EC



Risk Phrases

Safety Phrases

2.3 Other hazards

2.4 Additional Information

R65: Harmful: may cause lung damage if swallowed. R66: Repeated exposure may cause skin dryness or cracking. S2, S23, S24, S62. None. For full text of H/P phrases see section 16.

3. SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Mixtures

EC Classification No. 1272/2008

Hazardous ingredient(s)	%W/W	CAS No.	EC No.	REACH Registration No.	Hazard pictogram(s) and Hazard statement(s)
Kerosene – unspecified – distillates (petroleum), hydrotreated light	>90	64742-47-8	265-149-8	01-2119453414- 43-0001	GHS08, Asp. Tox. 1; H304, EUH066.

EC Classification No. 67/548/EEC

Hazardous ingredient(s)	%W/W	CAS No.	EC No.	REACH Registration No.	EC Classification and Risk Phrases
Kerosene – unspecified – distillates (petroleum), hydrotreated light	>90	64742-47-8	265-149-8	01-2119453414- 43-0001	Xn; R65, R66.

3.2 Additional Information

For full text of H/P phrases see section 16.

4. SECTION 4: FIRST AID MEASURES



4.1 Description of first aid measures Inhalation

Skin Contact

Eye Contact

Ingestion

- 4.2 Most important symptoms and effects, both acute and delayed
- 4.3 Indication of immediate medical attention and special treatment needed

If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, obtain medical attention.

Wash with plenty of soap and water. Remove contaminated clothing and wash clothing before reuse. If symptoms persist, obtain medical attention.

Flush eyes with water for at least 15 minutes while holding eyelids open. If symptoms persist, obtain medical attention. IF SWALLOWED: Do NOT induce vomiting. Immediately call a POISON CENTRE or doctor/physician.

Aspiration into the lungs may cause chemical pneumonitis, which can be fatal. Repeated exposure may cause skin dryness or cracking.

Unlikely to be required but if necessary treat symptomatically.



5. SECTION 5: FIRE-FIGHTING MEASURES

- 5.1 Extinguishing Media Suitable Extinguishing Media Unsuitable Extinguishing Media
- 5.2 Special hazards arising from the substance or mixture
- 5.3 Advice for fire-fighters

Extinguish with waterspray, foam or dry chemical. None known. None known.

Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Avoid spraying water directly into storage containers due to danger of boilover.

6. SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1	Personal precautions, protective equipment and emergency procedures	Ensure adequate ventilation. Avoid inhalation of high concentrations of vapours. Wear suitable protective clothing, gloves and eye/face protection.
6.2	Environmental precautions	Do not allow to enter drains, sewers or watercourses.
6.3	Methods and material for containment and cleaning up	Adsorb spillages onto sand, earth or any suitable adsorbent material. Transfer to a container for disposal.
6.4	Reference to other sections	See Also Section 8 and 13.
6.5	Additional Information	None.

7. SECTION 7: HANDLING AND STORAGE

7.1	Precautions for safe handling	Provide adequate ventilation. Avoid inhalation of high concentrations of vapours. Avoid prolonged skin contact. Wear suitable protective clothing, gloves and eye/face protection. Wash thoroughly with soap and water after handling. Do not eat, drink or smoke during work.
7.2	Conditions for safe storage, including any incompatibilities	Store locked up.
	Storage Temperature	Ambient.
	Storage Life	Stable under normal conditions.
	Incompatible materials	Strong oxidising agents, Natural rubber, Polystyrene, Butyl rubber.
7.3	Specific end use(s)	For use in the Magnetic Particle Inspection Process (BS EN ISO 9934-2:2002).

8. SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

8.1.1 Occupational Exposure Limits

SUBSTANCE.	CAS No.	LTEL (8 hr	LTEL (8 hr	STEL	STEL	Note:
		TWA ppm)	TWA mg/m³)	(ppm)	(mg/m³)	
Kerosene – unspecified – distillates (petroleum),	64742-47-8	150	1200	-	-	WEL (Reciprocal Calculation
hydrotreated light						Method)

WEL: Workplace Exposure Limit (UK HSE EH40)

8.1.2 Biological limit value

Not established.

Not established.

8.1.3 PNECs and DNELs



- 8.2 Exposure controls
- 8.2.1 Appropriate engineering controls
- 8.2.2 Personal protection equipment Eye/face protection



Skin protection (Hand protection/ Other)



Respiratory protection



Thermal hazards 8.2.3 Environmental Exposure Controls Provide adequate ventilation.

Wear protective eye glasses for protection against liquid splashes.

Wear suitable gloves if prolonged skin contact is likely. Impervious gloves (EN 374).

Not normally required.

Handling of larger amounts: A suitable mask with filter type A (EN14387 or EN405) may be appropriate. Use a respirator/filter with at least: PF10: 10 x Protection Factor. Not applicable. Do not allow to enter drains, sewers or watercourses.

9. SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical

properties Appearance Colour Odour Odour Threshold (ppm) pH (Value) Melting Point (°C) Boiling Point (°C)

Flash Point (°C) Evaporation rate Flammability Explosive limit ranges Vapour Pressure (mm Hg) Vapour Density (Air=1) Solubility (Water) Solubility (Water) Solubility (Other) Partition Coefficient (n-Octanol/water) Auto Ignition Temperature (°C) Decomposition Temperature (°C) Kinematic Viscosity Explosive properties Oxidising properties Other information Liquid. Green (Shaken). Paraffinic. Not available. Not applicable. Not applicable. 235 - 270°C. [Kerosene - unspecified - distillates (petroleum), hydrotreated light]. >100°C. Not available. Non-flammable. Not applicable. Not available. Not available. <0.10 wt%. Slightly soluble. Not available. Not available. >200°C. Not available. 3.2cSt. Not available. No information available. None.

10. SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

9.2

- 10.2 Chemical stability
- 10.3 Possibility of hazardous reactions
- 10.4 Conditions to avoid
- 10.5 Incompatible materials

Stable under normal conditions. Stable under normal conditions. Stable under normal conditions. Heat and direct sunlight. Strong oxidising agents, Natural rubber, Polystyrene, Butyl rubber.



10.6 Hazardous Decomposition Product(s) None known.

11. SECTION 11: TOXICOLOGICAL INFORMATION

11.1	Information on toxicological effects	
11.1.1	Mixtures	
	Acute toxicity	
	Ingestion	Low oral toxicity.
		Kerosene – unspecified – distillates (petroleum),
		hydrotreated light: LD50 (rat) : >15000mg/kg.
	Inhalation	Low acute toxicity.
		Kerosene – unspecified – distillates (petroleum),
		hydrotreated light: LC50 (rat) 4hour(s) : >4951mg/m ³ .
	Skin Contact	Low acute toxicity.
		Kerosene – unspecified – distillates (petroleum),
		hydrotreated light: LD50 (rabbit) : >2000mg/kg.
	Eye Contact	Low acute toxicity.
	skin corrosion/irritation	Repeated exposure may cause skin dryness or cracking.
	Serious eye damage/irritation	Not classified.
	Respiratory or skin sensitization	Not expected to be a skin or respiratory sensitiser.
	Repeated dose toxicity	None anticipated.
	Carcinogenicity	No evidence of carcinogenicity.
	Mutagenicity	There is no evidence of mutagenic potential.
	Reproductive toxicity	None anticipated.
	Aspiration hazard	Asp. Tox. 1; May be fatal if swallowed and enters airways.
		Aspiration into the lungs may cause chemical pneumonitis,
		which can be fatal.
11.2	Other information	None.

12. SECTION 12: ECOLOGICAL INFORMATION

12.1	Toxicity	Low toxicity to aquatic organisms.
12.2	Persistence and degradability	The product is not biodegradable. There is evidence of
		photodegradation in air. The product is unlikely to persist in
		the environment.
12.3	Bioaccumulative potential	The product has potential for bioaccumulation.
		Kerosene – unspecified – distillates (petroleum),
		hydrotreated light: BCF = 130-159.
12.4	Mobility in soil	Immiscible with water. The product is predicted to have low
		mobility in soil. The product is volatile and will partition into
		the atmosphere. Higher molecular weight hydrocarbons:
		The substance may adsorb onto soils and sediments.
12.5	Results of PBT and VPVB assessment	Not classified as PBT or vPvB.
12.6	Other adverse effects	None.
13. S	ECTION 13: DISPOSAL CONSIDERA	TIONS

13.1	Waste treatment methods	Dispose of contents/container to: Licensed recycler. Refer to manufacturer for information on recovery/recycling. Do NOT landfill.
13.2	Additional Information	Disposal should be in accordance with local, state or national legislation.

14. SECTION 14: TRANSPORT INFORMATION

Not classified as dangerous for transport.



- 14.1 UN number
- 14.2 Proper Shipping Name
- 14.3 Transport hazard class(es)
- 14.4 Packing Group
- 14.5 Environmental hazards
- 14.6 Special precautions for user
- 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code
- 14.8 Additional Information

Not applicable. Not applicable. Not applicable. Not applicable. Not applicable. Not applicable. Not applicable.

Not applicable.

15. SECTION 15: REGULATORY INFORMATION

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- **15.1.1 EU regulations** Authorisations and/or restrictions on use Other EU regulations

16. SECTION 16: OTHER INFORMATION

15.1.2 National regulations

15.2 Chemical Safety Assessment

None known. This product is not classified as a Volatile Organic Compound according to the Directive 1999/13/EC. None known. Not available.

The following sections contain revisions or new statements: 1-16.

LEGEND

LTEL	Long Term Exposure Limit
STEL	Short Term Exposure Limit
STOT	Specific Target Organ Toxicity
DNEL	Derived No Effect Level
PNEL	Predicted No Effect Concentration
PBT	PBT: Persistent, Bioaccumulative and Toxic
vPvB	vPvB: very Persistent and very Bioaccumulative
BCF	Bioconcentration factor
Asp. Tox. 1	Aspiration hazard Category 1
Xn	Harmful

Risk Phrases and Safety Phrases

- R65 Harmful: may cause lung damage if swallowed.
- R66 Repeated exposure may cause skin dryness or cracking.
- S2 Keep out of the reach of children.
- S23 Do not breathe vapour.
- S24 Avoid contact with skin.
- S62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Hazard statement(s)

H304	May be fatal if swallowed and enters airways.
EUH066	Repeated exposure may cause skin dryness or cracking.



Xn

Hazard pictogram(s) and Hazard Symbol GHS08



×

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Johnson and Allen Ltd gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Johnson and Allen Ltd accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

Annex to the extended Safety Data Sheet (eSDS)

No information available.