

Version 17.1 replaces Version 16.1 Revision date: 01.01.2017 According to (EU) No. 2015/830

SECTION 1

IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

1.1 Product identifier: SPOTCHECK® SKC-S

1.2 Relevant identified uses of the mixture and uses advised against:

Relevant identified uses: Solvent cleaner used in penetrant

inspection.

Uses advised against: This product is not recommended for any

use other than the identified uses above.

1.3 Details of the supplier of the safety data sheet

Manufacturer: Magnaflux® (A Division of ITW Ltd)

Address: Faraday Road, South Dorcan Industrial

Estate, Swindon, UK

Postcode: SN3 5HE

Telephone/fax number: Telephone: +44 (0)1793 524566

Fax: +44 (0)1793 490459 Web: www.eu.magnaflux.com

Email address of competent person datasheets@magnaflux.co.uk

responsible for SDS:

National contact: None appointed.

1.4 Emergency telephone number: DURING OFFICE HOURS, CALL

T: +44 (0)1793 524566 (English only)

Opening hours: Office hours (GMT) Monday - Thursday 8am

- 5pm, Friday 8am - 4pm

OUT OF OFFICE HOURS, CALL

T: +44(0)203 394 9866

SECTION 2 HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

Classification according to Regulation Physical and Chemical Hazard:

(EC) No 1272/2008 (CLP): Flam. Liq. 2 H225

Health Hazard: Skin Irrit. 2 H315 STOT SE 3 H336 Asp. Tox. 1 H304 Environmental Ha

Environmental Hazard: Aquatic Chronic 2 H411

Additional information No other information.

For full text of hazard statements and EU hazard statements see SECTION 16.

2.2 Label Elements:

Labelling according to regulation (EC) No 1272/2008 [CLP]

Hazard Pictograms:





Signal Word: DANGER

Hazard Statement(s): H225: Highly flammable liquid and vapour

H304: May be fatal if swallowed and enters

airways

H315: Causes skin irritation

H336: May cause drowsiness or dizziness H411: Toxic to aquatic life with long lasting

effects

Precautionary Statement(s): P243: Take precautionary measures against

static discharge

P273: Avoid release to the environment P280: Wear protective gloves/protective clothing/eye protection/face protection P301+330+331: IF SWALLOWED: Rinse

mouth. Do NOT induce vomiting

P302+352: IF ON SKIN: Wash with soap

and water

P403+235: Store in a well ventilated place.

Keep cool

Supplementary Precautionary

Statement(s):

P261: Avoid breathing

fume/gas/mist/vapours/spray.

P264: Wash thoroughly after handling. P301+P310: IF SWALLOWED: Immediately

call a POISON CENTRE or

doctor/physician.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P362+P364: Take off contaminated clothing

and wash it before reuse.

P501: Dispose of contents/container to hazardous waste or special collection point.

None

Supplementary Hazard Information

(EU)

Hazard Determining Component(s)

Hydrocarbons, C7 - C9, isoalkanes

2.3 Other hazards:

Physical/Chemical Hazards: Material can accumulate static charges which may cause an ignition. Material can release vapours that readily form flammable mixtures. Vapour accumulation could flash and / or explode if ignited.

Health Hazards: Repeated exposure may cause skin dryness or cracking. Irritating to skin. May be irritating to the eyes, nose, throat and lungs. May cause central nervous system depression.

Environmental Hazards: No additional hazards. Material does not meet the criteria for PBT or vPvB in accordance with REACH Annex XIII.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

3.1 **Substances**

| Name | Classification according to | Other information |
|----------------------------------|------------------------------|----------------------|
| | REGULATION (EC) No 1272/2008 | |
| Hydrocarbons, C7- C9, isoalkanes | Flam. Liq 2: H225 | No other information |
| | Skin Irrit. 2: H315 | |
| EC No 921-728-3 | STOT SE3: H336 | |
| REACH: 01-2119471305-42 | Asp. Tox. 1: H304 | |
| | Aquatic Chronic 2: H411 | |

Note: Hazard statement(s) in this section apply only to raw materials, not necessarily to finished

^{*}See Section 16 for hazard statement(s) text in full.

4.1 Description of first aid measures:

Following ingestion:

General notes: If symptoms persist, seek medical attention.

Show this safety data sheet to the doctor in

attendance.

Following inhalation: Remove to fresh air. Keep at rest. If not

breathing give artificial respiration. Seek prompt medical attention if discomfort

persists.

Flush with water, use soap if available. Following skin contact:

> Contaminated clothing should be washed before re-use. Seek medical attention if

irritation persists.

Flush eyes with large amounts of water for Following eye contact:

at least 15 minutes with eyelids held open. Seek medical attention if irritation persists. Rinse mouth with water. Do NOT induce vomiting. If vomiting occurs, keep head low

so that stomach contents don't enter the lungs. Never give anything by mouth to an

unconscious person. Seek medical

attention immediately.

Self-protection of the first aider: No action shall be taken involving any

personal risk or without suitable training. If it is suspected that the mixture is still present,

wear appropriate personal protective

equipment.

4.2 Most important symptoms, both acute and delayed:

Prolonged skin contact may cause redness and irritation.

In high concentrations, vapours are anaesthetic and may cause headache, fatique, dizziness and central nervous system effects.

Fumes from the stomach contents may be inhaled resulting in the same symptoms as inhalation. Avoid vomiting and normal rinse of stomach because of risk of aspiration.

Indication of any immediate medical attention and special treatment needed: 4.3

None known.

SECTION 5 FIREFIGHTING MEASURES

5.1 Extinguishing media:

5.2

Suitable extinguishing media: Carbon dioxide, foam, dry chemical, water

fog or spray.

Unsuitable extinguishing media:

Do not use water iet. Evacuate immediate area. Shut off 'fuel' to Special hazards arising from the

substance or mixture:

fire. Keep up-wind to avoid fumes. If possible keep unaffected containers cool with water spray. Avoid spraying water directly onto storage containers due to

danger of boil over.

Hazardous combustion products: Smoke, soot and oxides of carbon. Burning

vapour may give off toxic fumes.

5.3 Advice for fire-fighter:

Self contained breathing apparatus and full protective clothing must be worn.

Water spray should be used to cool containers.

Contaminated extinguishing water must be disposed of in accordance with official

regulations.

SECTION 6 ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Suitable protective equipment (see Section 8) should be worn to prevent any contamination of skin, eyes and personal clothing.

Remove ignition sources. Avoid breathing For non-emergency personnel:

vapours, mist or gas.

For emergency responders: Remove ignition sources. Avoid breathing

vapours, mist or gas. Keep unnecessary

people at a safe distance.

6.2 **Environmental precautions:**

> Prevent liquid from entering drains, sewers and watercourses. Notify the Environment Agency or water authorities if a major spillage occurs.

Methods and material for containment and cleaning up: 6.3

Eliminate sources of ignition. Avoid breathing vapours. Take measures to prevent the

build-up of electrostatic charge.

For containment: Contain spillage, and then collect with non-

combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite). Place in a UN approved container for

disposal.

Large spills should be pumped (using an earthed explosion proof pump) into UN approved containers pending disposal. Dispose of waste according to local/national

regulations.

For cleaning up: Do not flush away residues with water.

Other information: No other information.

6.4 Reference to other sections:

> For Personal Protective Equipment see Section 8. For disposal information see Section 13.

SECTION 7 HANDLING & STORAGE

7.1 Precautions for safer handling:

Protective Measures:Wear suitable protective clothing such as

chemical resistant gloves, apron and goggles/face mask to protect from splashes. Ensure adequate exhaust ventilation when

in use.

Avoid contact with skin and eyes. Do not breathe product spray or mist. Risk of vapour concentration in low areas.

Measures to prevent fire:Contents are highly flammable and volatile.

Keep away from sources of ignition. Wash thoroughly after handling.

Advice on general occupational

hygiene:

7.2

7.3

Conditions for safe storage, including any incompatibilities:

Technical measures and storageStore in a cool dry area away from heat and

conditions: sources of ignition.

Packaging materials: Store in original container. Keep containers

tightly closed when not in use.

Requirements for storage rooms and

vessels:

Recommended storage temperature 10 °C

to 30 °C.

Store locked up.

Keep containers out of direct sunlight. Rotate stock and check regularly for

Further information on storage conditions:

Conditions.

damaged items.

Specific end use(s):

Recommendations: Use only for Non Destructive Testing (NDT)

applications.

Industrial sector specific solutions: See product data sheet for further

information.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters:

Occupational exposure limit values:

Occupational exposure figures have been set for some of the components of this preparation based on GESTIS International Limit Values or manufacturers' recommendation.

| | | Limit value - 8 hours | | Limit value - short term | |
|--|---------|-----------------------|--------|--------------------------|--------|
| Ingredient name | Country | ppm | mg /m³ | ppm | mg /m³ |
| Hydrocarbons, C7 – C9, | UK | 241 | 1200 | | |
| isoalkanes | | | | | |
| Data obtained from GESTIS International Limit Values, EH40, supplier's SDS | | | | | |

Note: Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.

Derived No Effect Level (DNEL)

| End User | Exposure Route | Exposure Time | Effects | DNEL |
|----------|----------------|---------------|----------|------------------------|
| Worker | Inhalation | Long term | Systemic | 2035 mg/m ³ |
| Worker | Dermal | Long term | Systemic | 773 mg/kg bw/day |

Note: The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accordance with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a government regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygenists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH.

Predicted No Effect Concentration (PNEC)

Skin protection - other:

| Water - Fresh Water | No data available: testing technically not feasible |
|------------------------------|---|
| Water - Marine Water | No data available: testing technically not feasible |
| Water - Intermittent release | No data available: testing technically not feasible |
| Sediment - Fresh water | No data available: testing technically not feasible |
| Sediment - Marine water | No data available: testing technically not feasible |
| Soil | No data available: testing technically not feasible |
| Sewage Treatment plant | No data available: testing technically not feasible |

8.2 Exposure controls:

Concentrations of product vapours and mists in the working atmosphere must be kept as low as is reasonably practicable. Exposure should be minimised by the use of appropriate containment, engineering control and ventilation measures. Where this is not possible, personal protective equipment should be worn as indicated below where appropriate.

Appropriate engineering controls:

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limits are not exceeded

Personal protection equipment:
Eye and face protection:

Safety glasses with side-shields conforming to EN166.

Skin protection - hand:

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limits are not exceeded

Safety glasses with side-shields conforming to EN166.

Protective gloves conforming to EN374-3. Use chemical resistant gloves recommended by glove manufacturer as being suitable for **isoparaffins**, if hand exposure is unavoidable.

Protective gloves made of **nitrile rubber**

are suitable, although other types may be more suitable in other circumstances. For prolonged exposure, recommended gloves with protective index 6, > 480 minutes permeation time according to EN374.

Consult the glove manufacturer for exact breakthrough time. Glove manufacturer's directions for use should be observed. Wear impervious, flame retardant antistatic protective clothing. The type of protective equipment must be selected according to the concentration and amount of dangerous substance at the

specific workplace.

Respiratory protection: In case of insufficient ventilation, wear

suitable respiratory equipment. Filter type

A. (EN 136, 140, 405, 149, 143)
For higher level protection use type
ABEK-P3 (EU EN 143) respirator
cartridges. Use respirators and

components tested and approved under

CEN standards.

Thermal hazards: Not applicable.

Environmental exposure controls: Avoid any release to the environment.

SECTION 9 PHYSICAL & CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

Appearance:Mobile clear liquid.Odour:Mild hydrocarbon.Odour threshold:No data available.

pH: Neutral.

Melting point/freezing point: No data available. Initial boiling point and boiling range: 113 - 143 °C.

Flash point (PMCC): 7 °C. Evaporation rate (BuAc = 100): 155.

Flammability (solid, gas) (Limits in air): No data available. Upper/lower flammability or explosive 0.7 – 6.0% (Vol%)

limits:

Vapour pressure: 1.627 kPa @ 20 °C.

Vapour density (Air = 1): > 1.

Relative density: 0.72 g/cm³. **Solubility:** Insoluble.

Partition coefficient: n-octanol/water: No data available.

Auto-ignition temperature: > 200 °C.

Decomposition temperature:No data available. **Viscosity (ASTM D445):**0.86 mm²/s @ 25 °C.

Explosive properties: Under normal conditions no danger of

explosion.

Oxidising properties: No data available.

Note: properties relate to the bulk product only unless otherwise stated.

9.2 Other information:

No other information.

| SECTION 10 | STABILITY & REACTIVITY |
|------------|------------------------|
| SECTION ID | SIADILII & NLACIIVII I |

| 10.1 | Reactivity: | No specific reactivity hazards associated with this product. |
|------|-------------------------------------|--|
| 10.2 | Chemical stability | Stable under normal conditions of use and applications. |
| 10.3 | Possibility of hazardous reactions: | No data available. |
| 10.4 | Conditions to avoid: | Keep away from sources of ignition, hot surfaces and direct sun light. |
| 10.5 | Incompatible materials: | Strong oxidising agents. |
| 10.6 | Hazardous decomposition materials: | None under normal conditions of use. |

combustion.

Smoke, soot and oxides of carbon on

SECTION 11 TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects: based on data for component materials.

Acute toxicity - oral: Based on the available data, the classification

criteria are not met.

Acute toxicity – dermal: Based on the available data, the classification

criteria are not met.

Acute toxicity – inhalation: Based on the available data, the classification

criteria are not met.

Skin corrosion/irritation: Skin Irrit. 2 H315: Causes skin irritation.

Serious eye damage/irritation: Based on the available data, the classification

criteria are not met.

Respiratory sensitisation: Data lacking.

Skin sensitisation: Based on the available data, the classification

criteria are not met.

Germ cell mutagenicity:Based on the available data, the classification

criteria are not met.

Carcinogencity: Data lacking.

Reproductive toxicity: Based on the available data, the classification

criteria are not met.

STOT single exposure: STOT Single Exp. 3 H336: May cause

drowsiness or dizziness.

Affected organs: central nervous system

Route of exposure: inhalation

STOT repeated exposure: Based on the available data, the classification

criteria are not met.

Aspiration hazard: Asp. Tox. 1 H304: May be fatal if swallowed

and enters airways.

Information on likely Routes of Exposure and Potential Health Effects:

Inhalation: Vapour concentrations above the

recommended exposure levels are irritating to the eyes and respiratory tract, may cause headaches and dizziness, are anaesthetic and may have other central nervous system

effects.

Ingestion: Harmful: May cause lung damage if

swallowed. Ingestion may cause irritation of the mouth, throat and digestive tract. Small amounts of product aspirated into the respiratory system during ingestion or from vomiting may cause bronochopneumonia or

pulmonary edema.

Eye contact: May cause redness and pain.

Skin contact: Frequent or prolonged contact with the

product may produce irritation and/or skin dryness and cracking. Product will have a de-

fatting effect on the skin.

Toxicity Test Results: based on data for component materials, where available.

| Acute Toxicity – oral | LD50 (rat) | > 5000 mg/kg |
|-----------------------------|---------------|-----------------------|
| Acute Toxicity – dermal | LD50 (rabbit) | > 2000 mg/kg |
| Acute Toxicity – inhalation | LC50 (rat) | 21 mg/l (4 h; vapour) |

Other Information: No other information.

SECTION 12 ECOLOGICAL INFORMATION

Based on data for component materials

12.1 Toxicity:

| Fish | Oncorhynchus mykiss | LL50 | 96h | 18.4 mg/l |
|-----------------------|---------------------------------|------|-----|-----------|
| Aquatic Invertebrates | Daphnia magna | EL50 | 48h | 2.4 mg/l |
| Aquatic Plants | Pseudokirchneriella subcapitata | EL50 | 72h | 29 mg/l |

12.2 Persistence and degradability: Biodegradable.

12.3 Bioaccumulative potential: No data available.

Partition coefficient: n-octanol/water

(log Kow):

No data available.

Bioconcentration factor (BCF): No data available.

12.4 Mobility in soil: The product is immiscible with water and will

spread on the water surface. Product is highly volatile - will partition rapidly to air.

12.5 Results of PBT and vPvB assessment: This mixture does not contain any

substances that are assessed to be a PBT or

vPvB.

12.6 Other adverse effects: No data available.

SECTION 13 DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Dispose of waste and residues in accordance with local authority requirements. Seek the advice of an approved waste disposal contractor for disposal at a licensed facility in accordance with national legislation.

Product/packing disposal: Empty containers may contain residue and

can be dangerous. Do NOT remove labels. Keep away from sources of

ignition.

Waste codes/waste designations

according to LoW:

None assigned.

NOTE: Waste codes are assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use. Waste producers need to assess the actual process used when generating the waste and its contaminants in order to assign the proper waste code(s).

Waste treatment - relevant information: Dispose of waste and residues in

accordance with local authority requirements. Seek the advice of an approved waste disposal contractor for disposal at a licensed facility in

accordance with national legislation.

Do not empty down the drain.

Sewage disposal - relevant

information:

Other disposal recommendations: Use a licensed waste contractor

SECTION 14 TRANSPORT INFORMATION

14.1 **UN number:** ADR/RID: UN3295 IMDG: UN3295

IATA: UN3295

14.2 **UN proper shipping name:** ADR/RID: HYDROCARBONS.

LIQUID, N.O.S (HYDROCARBONS, C7-C9

ISOALKANES)

IMDG: HYDROCARBONS,

LIQUID, N.O.S (HYDROCARBONS, C7-C9

ISOALKANES)

IATA: HYDROCARBONS,

LIQUID, N.O.S (HYDROCARBONS, C7-C9

ISOALKANES)

14.3 Transport hazard class(es): ADR/RID: 3

IMDG: 3 IATA: 3

14.4 ADR/RID: Packing group: Ш

IMDG: Ш Ш IATA:

ADR/RID: 14.5 **Environmental hazards:** Yes

> Marine Pollutant: Yes IMDG:

IATA: Yes

14.6 Special precautions for user:

Proper Shipping Name Suffix: Special Provision 640D

Label(s) / Mark(s): 3, EHS Classification Code: F1 Hazard ID No (ADR/RID): 33

Tunnel Restriction Code (ADR): D/E EMS Number (IMDG): F-E, S-D

Hazchem EAC: 3YE

14.7 Transport in bulk according to Annex II of Marpol 73/78 and the IBC code:

Substance Name: ALKANES (C6-C9)

Ship type required: 2 Pollution category: X

SECTION 15 REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EU Regulations:

This data sheet complies with the requirements of Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures.

Safety data sheet as required by EC-Regulations 1907/2006 and REACH Annex II Amendment (EU) No. 2015/830.

Information according to 2013/10/EU and 2008/47/EC amendment of the aerosol directive 75/324/EEC.

Not applicable - this product is not an aerosol.

National regulations (Germany):

Wassergefahrdungklasse (water WGK 2 - Hazard to waters.

hazard class):

Technische Anleitung Luft (TA-Luft): Chapter 5.2.5 Organic Substances, except

dusts

15.2 Chemical safety assessment:

No data available.

SECTION 16 OTHER INFORMATION

(i) Indication of changes:

Version 17.1 updated in Section 1.4.

Vertical lines on the left hand side indicate an amendment from the previous version.

(ii) Abbreviations and acronyms:

ADR European Agreement concerning the International Carriage of Dangerous Goods

by Road (Accord européen relatif au transport international des marchandises

Dangereuses par Route)

CAS No. Chemical Abstracts Service number
CEN European Committee for Standardisation

CLP Classification, Labelling Packaging Regulation; Regulation (EC) No 1272/2008

ECHA European Chemicals Agency
EC50 Half Maximal Effective Concentration

EC number EINECS and ELINCS number

EINECS European Inventory of Existing Commercial Substances

ELINCS European List of notified Chemical Substances

GHS Globally Harmonized System

IATA International Air Transport Association
IMDG International Maritime Dangerous Goods

LC50 Lethal Concentration to 50% of a test population

LD50 Lethal Dose to 50% of a test population

MPI Magnetic Particle Inspection
NDT Non-Destructive Testing
OEL Occupational Exposure Limit

PBT Persistent, Bioaccumulative and Toxic Substance

PMCC Pensky-Martens closed cup method PPE Personal Protection Equipment

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation

EC (No) 1907/2006

RID Regulations concerning the International Carriage of Dangerous Goods by Rail

(Reglement International concernant le transport des marchandises Dangereuses

par chemin de fer) Safety Data Sheet

STOT RE Specific Target Organ Toxicity, Repeat Exposure STOT SE Specific Target Organ Toxicity, Single Exposure

TA-Luft Technical Instructions on Air Quality Control (Technische Anleitung zur

Reinhaltung der Luft)

vPvB Very Persistent and Very Bioaccumulative

WEL Workplace Exposure Limit

WGK German Water Hazard Class (Wassergefährdungsklasse)

(iii) Key literature and sources of data:

SDS

• Supplier's safety data sheets for components listed in Section 3.

• European Chemicals Agency, http://echa.europa.eu/

 GESTIS International Limit Values Database, http://limitvalue.ifa.dguv.de/Webform_gw.aspx

- Occupational Exposure Limits EH40/2005.
- Commission regulation (EU) 2015/830.
- Control of Substances Hazardous to Health Regulations 2002.
- Hazardous waste regulations 2005.
- Health & Safety at Work Act 1974.
- Regulation (EC) No. 1907/2006 (REACH).
- Regulation (EC) No. 1272/2008 (CLP).

(iv) Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 (CLP):

Not applicable – this product is regulated as a substance.

(v) Hazard statements (number and full text):

H225: Highly flammable liquid and vapour

H304: May be fatal if swallowed and enters airways

H315: Causes skin irritation

H336: May cause drowsiness or dizziness

H411: Toxic to aquatic life with long lasting effects

Hazard Class and Category Code (full text):

Aquatic Chronic 2: Hazardous to the aquatic environment

Asp. Tox. 1: Aspiration hazard Flam. Liq. 2: Flammable liquid Skin Irrit. 2: Skin corrosion/irritation

STOT SE 3: Specific target organ toxicity - single exposure

Relevant precautionary statements (number and full text):

P243: Take precautionary measures against static discharge

P273: Avoid release to the environment

P280: Wear protective gloves/protective clothing/eye protection/face protection

P301+330+331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P302+352: IF ON SKIN: Wash with soap and water P403+235: Store in a well ventilated place. Keep cool

P261: Avoid breathing fume/gas/mist/vapours/spray.

P264: Wash thoroughly after handling.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P362+P364: Take off contaminated clothing and wash it before reuse.

P501: Dispose of contents/container to hazardous waste or special collection point.

(vi) Training advice:

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene. Chemical hazard risk assessment.

Provide adequate information, instruction and training to operators.

DISCLAIMER

The information and recommendations contained herein are based upon data believed to be up-to-date and correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information and recommendations contained herein. We accept no responsibility and disclaim all liability for any harmful effects that may be caused by (incorrect) use, handling, purchase, resale, or exposure to our product. Customers and users of our product must comply with all applicable health and safety laws, regulations, and orders. In particular, they are under an obligation to carry out a risk assessment for the particular work places and to take adequate risk management measures in accordance with the national implementation legislation of EU Directives 89/391/EEC and 98/24/EC amended by Directive 2014/27/EU.

Revision Revision This SDS is valid from the Revision Date. If you require a SDS for summary: Comments the product manufactured before the Revision Date please contact

us at datasheets@magnaflux.co.uk.

Revision Date 01.01.2017

Version 17.1