

SAFETY DATA SHEET

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 453/2010

1. SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Product Name NEOCOL B - AEROSOL.

CAS No. Mixture.
EINECS No. Mixture.
REACH Registration No. None assigned.

1.2 Relevant identified uses of the substance or

mixture and uses advised against

Identified use(s) A Black Magnetic Ink for use in the Magnetic Particle

Inspection Process (BS EN ISO 9934-2:2002).

Uses advised against None known.

1.3 Details of the supplier of the Safety Data

Sheet

1.4

Company Identification Johnson and Allen Ltd

Neocol Works Smithfield Sheffield S3 7AR. 0114 2738066.

Telephone 0114 2738066.
Fax 0114 2729842.
E-Mail (competent person) info@johnsonandallen.co.uk

E-Mail (competent person)

Emergency telephone number

Emergency Phone No. 0114 2738066. (UK office hours 08.30-17.00).

2. SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

2.1.1 Regulation (EC) No. 1272/2008 (CLP) Aerosol 3; Pressurised container: May burst if heated.

Asp. Tox. 1; May be fatal if swallowed and enters airways. Repeated exposure may cause skin dryness or cracking. Xn; Harmful: may cause lung damage if swallowed.

2.1.2 Directive 67/548/EEC & Directive 1999/45/EC

Repeated exposure may cause skin dryness or cracking.

2.2 Label elements According to Regulation (EC) No. 1272/2008 (CLP)

Product Name Hazard Pictogram NEOCOL B – AEROSOL.

CHSUS

Signal word(s) Danger.

Hazard statement(s) H229: Pressurised container: May burst if heated.

H304: May be fatal if swallowed and enters airways. EUH066: Repeated exposure may cause skin dryness or

cracking.

Revision: 5 Page: 1/8 Date: 08/08/2014



Precautionary statement(s) P210: Keep away from heat, hot surfaces, sparks, open

None.

flames and other ignition sources. No smoking. P251: Do not pierce or burn, even after use.

P301+P310: IF SWALLOWED: Immediately call a POISON

CENTER/doctor.

P331: Do NOT induce vomiting..

P405: Store locked up.

P410+P412: Protect from sunlight. Do no expose to

temperatures exceeding 50°C/ 122°F.

2.3 Other hazards

2.4 Additional Information For full text of H/P phrases see section 16.

3. SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Product as supplied: Aerosol.

3.1 Mixtures

EC Classification No. 1272/2008

| Hazardous ingredient(s) | %W/W | CAS No. | EC No. | REACH Registration No. | Hazard pictogram(s) and Hazard statement(s) |
|--|------|------------|-----------|---------------------------|---|
| Kerosene – unspecified – distillates (petroleum), hydrotreated light | >90 | 64742-47-8 | 265-149-8 | 01-2119453414- 43-0001 | GHS08, Asp. Tox. 1; H304, EUH066 |
| Carbon dioxide | 1-10 | 124-38-9 | 204-696-9 | None assigned | GHS04, Press. Gas; H280 |
| Triiron tetraoxide | <1 | 1317-61-9 | 215-277-5 | 01-2119457646- 28-0000 | None |

EC Classification No. 67/548/EEC

| Hazardous | %W/W | CAS No. | EC No. | REACH | EC Classification and |
|--------------------------|------|------------|-----------|------------------|-----------------------|
| ingredient(s) | | | | Registration No. | Risk Phrases |
| Kerosene – | >90 | 64742-47-8 | 265-149-8 | 01-2119453414- | Xn; R65, R66. |
| unspecified – | | | | 43-0001 | |
| distillates (petroleum), | | | | | |
| hydrotreated light | | | | | |
| Carbon dioxide | 1-10 | 124-38-9 | 204-696-9 | None assigned | None |
| Triiron tetraoxide | <1 | 1317-61-9 | 215-277-5 | 01-2119457646- | None |
| | | | | 28-0000 | |

3.2 Additional Information

For full text of H/P phrases see section 16.

Revision: 5 Page: 2/8 Date: 08/08/2014



4. SECTION 4: FIRST AID MEASURES



Description of first aid measures

Inhalation If breathing is difficult, remove victim to fresh air and keep at

rest in a position comfortable for breathing. If symptoms

persist, obtain medical attention.

Skin Contact Wash with plenty of soap and water. Remove contaminated

clothing and wash clothing before reuse. If symptoms persist,

obtain medical attention.

Flush eyes with water for at least 15 minutes while holding

eyelids open. If symptoms persist, obtain medical attention. IF SWALLOWED: Do NOT induce vomiting. Immediately call

a POISON CENTER/doctor.

4.2 Most important symptoms and effects, both Aspiration into the lungs may cause chemical pneumonitis, acute and delayed

which can be fatal. Repeated exposure may cause skin

dryness or cracking.

4.3 Indication of any immediate medical attention Unlikely to be required but if necessary treat symptomatically.

and special treatment needed

5. SECTION 5: FIRE-FIGHTING MEASURES

Pressurised container: May burst if heated.

5.1 **Extinguishing Media**

5.2

Eye Contact

Ingestion

Suitable Extinguishing Media Unsuitable Extinguishing Media

Special hazards arising from the substance or

5.3 Advice for fire-fighters

mixture

Extinguish with waterspray, foam or dry chemical.

None known.

Heating may cause pressure rise with risk of bursting.

Fire fighters should wear complete protective clothing including self-contained breathing apparatus. If it is safe to do so, containers should be removed from fire area because they are likely to rupture under fire conditions. Keep containers cool by spraying with water if exposed to fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

The product is an aerosol. It is unlikely to present spillage or leakage hazard. In case of rupture, released content should be contained as any other solvent spill.

Ensure adequate ventilation. Avoid inhalation of high 6.1 Personal precautions, protective equipment concentrations of vapours. Wear suitable gloves and and emergency procedures

eye/face protection.

6.2 **Environmental precautions** Do not release large quantities into the surface water or into

6.3 Methods and material for containment and Collect mechanically and dispose of according to Section 13. cleaning up Adsorb spillages onto sand, earth or any suitable adsorbent

material. Transfer to a lidded container for disposal or recovery. Containers must not be punctured or destroyed by

burning, even when empty.

6.4 Reference to other sections See Also Section 8 and 13.

Revision: 5 Page: 3/8 Date: 08/08/2014



7. SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling Keep away from heat, hot surfaces, sparks, open flames and

other ignition sources. No smoking. Do not pierce or burn, even after use. Provide adequate ventilation. Avoid inhalation of high concentrations of vapours. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke during work.

Wash hands thoroughly after handling. Store locked up. Protect from sunlight.

7.2 Conditions for safe storage, including any

incompatibilities

Storage Temperature

Ambient. Do not expose to temperatures exceeding 50°C/

122°F.

Storage Life Stable under normal conditions.

Incompatible materials Strong oxidising agents, Natural rubber, Polystyrene, Butyl

rubber.

7.3 Specific end use(s) A Black Magnetic Ink for use in the Magnetic Particle

Inspection Process (BS EN ISO 9934-2:2002).

8. SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

8.1.1 Occupational Exposure Limits

| SUBSTANCE. | CAS No. | LTEL (8 hr | LTEL (8 hr | STEL | STEL | Note |
|--------------------------|------------|------------|------------|-------|---------|-----------------|
| | | TWA ppm) | TWA mg/m³) | (ppm) | (mg/m³) | |
| Kerosene – unspecified – | 64742-47-8 | 150 | 1200 | - | - | WEL (Reciprocal |
| distillates (petroleum), | | | | | | Calculation |
| hydrotreated light | | | | | | Method) |
| Carbon dioxide | 124-38-9 | 5000 | 9150 | 15000 | 27400 | WEL |

WEL: Workplace Exposure Limit (UK HSE EH40)

8.1.2 Biological limit value Not established.

8.1.3 PNECs and DNELs Not established.

8.2 Exposure controls

8.2.1 Appropriate engineering controls Provide adequate ventilation.

8.2.2 Personal protection equipment

Eye/face protection Wear suitable eye/face protection.

Skin protection (Hand protection/ Other) Wear suitable protective clothing and gloves.

Respiratory protection

required. Handling of larger amounts: In case of insufficient ventilation, wear suitable respiratory equipment. A suitable mask with filter type A (EN14387 or EN405) may be appropriate. Use a respirator/filter with at least: PF10: 10 x

No personal respiratory protective equipment normally

Protection Factor.

Thermal hazards Not applicable.

Revision: 5 Page: 4/8 Date: 08/08/2014



8.2.3 Environmental Exposure Controls Do not release large quantities into the surface water or into

drains.

9. SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical

properties

Appearance Aerosol.

Colour Dark grey/Black (Shaken).

Odour Paraffinic.
Odour Threshold Not available.
pH Not applicable.
Melting Point/Freezing Point Not applicable.
Initial boiling point and boiling range 235 - 270°C
Flash Point >100°C
Evaporation rate Not applicable.

Flammability (solid, gas)

Upper/lower flammability or explosive limits

Not applicable.

Non-flammable.

Not applicable.

Vapour pressure 0.015 mm Hg @ 20°C

Vapour density Not available.

Relative density 0.82

Solubility(ies) Immiscible with water.

Partition coefficient: n-octanol/water Not available.

Auto-ignition temperature Not applicable.

Decomposition Temperature Not available.

Kinematic Viscosity 3.2cSt @ 40°C

Explosive properties Pressurised container: May burst if heated.

Oxidising properties No information available.

9.2 Other information None.

10. SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity Stable under normal conditions.
 10.2 Chemical stability Stable under normal conditions.
 10.3 Possibility of hazardous reactions Stable under normal conditions.
 10.4 Conditions to avoid Heat and direct sunlight.

10.5 Incompatible materials Strong oxidising agents, Natural rubber, Polystyrene, Butyl

rubber.

10.6 Hazardous Decomposition Product(s) None known.

11. SECTION 11: TOXICOLOGICAL INFORMATION

Unlikely to cause harmful effects under normal conditions of handling and use.

11.1 Information on toxicological effects

11.1.1 Mixtures

Acute toxicity

Ingestion Low oral toxicity.

Kerosene - unspecified - distillates (petroleum),

hydrotreated light: LD50 (rat) >5000mg/kg

Inhalation Low acute toxicity.

Kerosene - unspecified - distillates (petroleum),

hydrotreated light: LC50 (rat) 4hour(s) >5.28mg/l

Skin Contact Low acute toxicity.

Kerosene – unspecified – distillates (petroleum),

hydrotreated light: LD50 (rabbit) >2000mg/kg

Eye Contact Low acute toxicity.

Revision: 5 Page: 5/8 Date: 08/08/2014



Irritation Repeated exposure may cause skin dryness or cracking.

Corrosivity Not classified.

Sensitisation Not expected to be a skin or respiratory sensitiser.

Repeated dose toxicity None anticipated.

Carcinogenicity No evidence of carcinogenicity.

Mutagenicity There is no evidence of mutagenic potential.

Toxicity for reproductionNone anticipated.

Aspiration hazard Asp. Tox. 1; May be fatal if swallowed and enters airways.

Aspiration into the lungs may cause chemical pneumonitis,

which can be fatal.

11.2 Other information None.

12. SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity Low toxicity to aquatic organisms.

Kerosene - unspecified - distillates (petroleum),

hydrotreated light:

Fish: LC50 (96 hour) = 45mg/l

Aquatic invertebrates: EC50 (48 hour) = 4720mg/l

12.2 Persistence and degradability The product is not biodegradable. There is evidence of

photodegradation in air. The product is unlikely to persist in

the environment.

12.3 Bioaccumulative potential The product has potential for bioaccumulation.

Kerosene - unspecified - distillates (petroleum),

hydrotreated light: BCF = 130-159.

12.4 Mobility in soil Immiscible with water. The product is predicted to have low

mobility in soil. The product is volatile and will partition into the atmosphere. Higher molecular weight hydrocarbons: The substance may adsorb onto soils and sediments.

12.5 Results of PBT and VPVB assessment Not classified as PBT or vPvB.

12.6 Other adverse effects None.

13. SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods Recycle only completely emptied packaging. Containers

must not be punctured or destroyed by burning, even when empty. Non-emptied aerosol: Dispose of wastes in an approved waste disposal facility. Refer to manufacturer for information on recovery/recycling. Do NOT landfill.

Disposal should be in accordance with local, state or

national legislation.

14. SECTION 14: TRANSPORT INFORMATION

Additional Information

14.1 UN number UN 195014.2 Proper Shipping Name AEROSOLS.

14.3Transport hazard class(es)214.4Packing GroupNone.14.5Environmental hazardsNone.14.6Special precautions for userNone.

14.7 Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code

Not applicable.

14.8 Additional Information

13.2

14.8.1ADR Classification Code5A14.8.2Hazard label(s)2.2

Revision: 5 Page: 6/8 Date: 08/08/2014



15. SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental

regulations/legislation specific for the

substance or mixture

15.1.1 EU regulations

Authorisations and/or restrictions on use

Candidate List of Substances of Very High All chemicals are not listed.

Concern for Authorisation

REACH: ANNEX XVII Restrictions on the All chemicals are not listed.

manufacture, placing on the market and use of certain dangerous substances, mixtures and

articles

REACH: ANNEX XIV List of substances subject to All chemicals are not listed.

authorisation

Community Rolling Action Plan (CoRAP); All chemicals are not listed.

Draft 20/03/2012

15.1.2 National regulations None known.
 15.2 Chemical Safety Assessment Not available.

16. SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

LEGEND

LTEL Long Term Exposure Limit
STEL Short Term Exposure Limit
STOT Specific Target Organ Toxicity
DNEL Derived No Effect Level

PNEL Predicted No Effect Concentration

PBT PBT: Persistent, Bioaccumulative and Toxic vPvB vPvB: very Persistent and very Bioaccumulative

BCF Bioconcentration factor
Aerosol 3 Aerosol Category 3
Asp. Tox. 1 Aspiration hazard Category 1

Press. Gas Gases under pressure: Compressed gas

Xn Harmful

Risk Phrases and Safety Phrases

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

Hazard statement(s)

H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways.

EUH066 Repeated exposure may cause skin dryness or cracking.

Revision: 5 Page: 7/8 Date: 08/08/2014



Xn

Hazard pictogram(s) and Hazard Symbol

GHS04

GHS08



Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. Johnson and Allen Ltd gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. Johnson and Allen Ltd accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

Annex to the extended Safety Data Sheet (eSDS)

No information available.

Revision: 5 Page: 8/8 Date: 08/08/2014