

SAFETY DATA SHEET



Version 17.1 replaces Version 16.1
Revision date: 01.01.2017
According to (EU) No. 2015/830

SECTION 1

IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

- 1.1 Product identifier:** SPOTCHECK® SKD-S2
- 1.2 Relevant identified uses of the mixture and uses advised against:**
Relevant identified uses: Solvent developer used in penetrant inspection.
Uses advised against: This product is not recommended for any use other than the identified uses above.
- 1.3 Details of the supplier of the safety data sheet**
Manufacturer: Magnaflux® (A Division of ITW Ltd)
Address: Faraday Road, South Dorcan Industrial Estate, Swindon, UK
Postcode: SN3 5HE
Telephone/fax number: Telephone: +44 (0)1793 524566
Fax: +44 (0)1793 490459
Web: www.eu.magnaflux.com
Email address of competent person responsible for SDS: datasheets@magnaflux.co.uk
National contact: None appointed.
- 1.4 Emergency telephone number:** DURING OFFICE HOURS, CALL
T: +44 (0)1793 524566 (English only)
Opening hours: Office hours (GMT) Monday - Thursday 8am - 5pm, Friday 8am - 4pm
OUT OF OFFICE HOURS, CALL
T: +44(0)203 394 9866

SECTION 2

HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
Classification according to Regulation (EC) No 1272/2008 (CLP): **Physical and Chemical Hazard:** Flam. Liq. 2 H225
Health Hazard: Eye Irrit. 2 H319
STOT SE 3 H336
Environmental Hazard: None
Additional information EUH066

For full text of hazard statements and EU hazard statements see SECTION 16.

SAFETY DATA SHEET

2.2

Label Elements:

Labelling according to regulation (EC) No 1272/2008 [CLP]

Hazard Pictograms:



Signal Word:

Danger

Hazard Statement(s):

H225: Highly flammable liquid and vapour

H319: Causes serious eye irritation

H336: May cause drowsiness or dizziness

Precautionary Statement(s):

P210: Keep away from heat/sparks/open flames/hot surfaces – No smoking

P261: Avoid breathing

dust/fume/gas/mist/vapours/spray

P280: Wear protective gloves/protective clothing/eye protection/face protection

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses if present and easy to do – continue rinsing

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P370+P378: IN CASE OF FIRE: Use carbon dioxide, foam, dry chemical, water fog or spray for extinction

Supplementary Precautionary Statement(s):

P243: Take precautionary measures against static discharge.

P264: Wash thoroughly after handling

P271: Use only outdoors or in a well-ventilated area

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

P337+P313: If eye irritation persists get medical advice/attention

P403+P233: Store in a well ventilated place. Keep container tightly closed

P501: Dispose of contents/container to hazardous waste or special collection point.

EUH066

Supplementary Hazard Information (EU)

Hazard Determining Component(s)

Acetone, Propan-2-ol

2.3

Other hazards:

Vapours can form explosive mixtures in air.

SAFETY DATA SHEET

SECTION 3

COMPOSITION / INFORMATION ON INGREDIENTS

3.2 Mixtures

Ingredient Name	CAS No	EC No	REACH Registration Number	% Weight	Classification according to Regulation (EC) No 1272/2008 [CLP]	Additional information
Propan-2-ol	67-63-0	200-661-7	01-2119457558-25	< 75	Flam. Liq 2 H225 Eye Irrit. 2 H319 STOT SE3 H336	None
Acetone	67-64-1	200-662-2	01-2119471330-49	< 25	Flam. Liq 2 H225 Eye Irrit. 2 H319 STOT SE3 H336	EUH066
Talc	14807-96-6	238-877-9	Exempted in accordance with Annex V.7	< 3	Not classified	Has WEL
Aluminium Hydroxide	21645-51-2	244-492-7	01-2119529246-39	< 3	Not classified	Has WEL
Calcium Carbonate	471-34-1	207-439-9	01-2119486795-18	< 3	Not classified	Has WEL

Note: Hazard statement(s) in this section apply only to raw materials, not necessarily to finished products.

**See Section 16 for hazard statement(s) text in full.*

SECTION 4

FIRST AID MEASURES

4.1 Description of first aid measures:

General notes:

If symptoms persist, seek medical attention. Show this safety data sheet to the doctor in attendance.

Following inhalation:

Remove to fresh air. Keep at rest. If not breathing give artificial respiration. Seek medical attention if symptoms occur.

Following skin contact:

Flush with water, use soap if available. Take off contaminated clothing and wash before re-use. Seek medical attention if irritation persists.

Following eye contact:

Flush eyes with large amounts of water for at least 10 minutes. Check for and remove any contact lenses if easy to do. Continue rinsing. Seek medical attention if irritation persists.

Following ingestion:

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth thoroughly. Seek medical attention if symptoms occur.

Self-protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. If it is suspected that the mixture is still present, wear appropriate personal protective equipment.

4.2 Most important symptoms, both acute and delayed:

Irritation to eyes. No delayed effects known.

4.3 Indication of any immediate medical attention and special treatment needed:

None known.

SAFETY DATA SHEET

SECTION 5

FIREFIGHTING MEASURES

- 5.1 Extinguishing media:**
Suitable extinguishing media: Carbon dioxide, foam, dry chemical, water fog or spray.
- 5.2 Unsuitable extinguishing media:** Do not use water jet.
Special hazards arising from the substance or mixture: Evacuate immediate area. Shut off 'fuel' to fire. If possible, keep unaffected containers cool with water spray.
Hazardous combustion products: Smoke, soot and oxides of carbon. Burning vapour may give off toxic fumes.
- 5.3 Advice for fire-fighter:**
Cool containers exposed to flames with water until well after the fire is out. Self contained breathing apparatus and full protective clothing must be worn. Fire water run-off must not be allowed to contaminate ground, or enter drains, sewers or water courses.

SECTION 6

ACCIDENTAL RELEASE MEASURES

- 6.1 Personal precautions, protective equipment and emergency procedures:**
Suitable protective equipment (see Section 8) should be worn to prevent any contamination of skin, eyes and personal clothing.
For non-emergency personnel: Remove ignition source. Avoid breathing vapours, mist or gas. Ensure adequate ventilation.
For emergency responders: Keep unnecessary people at a safe distance. Remove ignition source. Avoid breathing vapours, mist or gas. Ensure adequate ventilation.
- 6.2 Environmental precautions:**
Prevent liquid from entering drains, sewers and watercourses. Notify the Environment Agency or water authorities if a major spillage occurs. Prevent product from contaminating soil.
- 6.3 Methods and material for containment and cleaning up:**
Ventilate well. Eliminate sources of ignition. Take measures to prevent the build-up of electrostatic charge.
For containment: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite). Place in a UN approved container for disposal.
Large spills should be pumped (using an earthed explosion proof pump) into UN approved containers pending disposal. Dispose of waste according to local/national regulations.
For cleaning up: Rinse site with copious amounts of water, which should not be allowed into drains, sewers or watercourses.
- 6.4 Other information:** No other information.
Reference to other sections:
For Personal Protective Equipment see Section 8. For disposal information see Section 13.

SAFETY DATA SHEET

SECTION 7

HANDLING & STORAGE

7.1	Precautions for safer handling: Protective Measures:	Wear suitable protective clothing such as chemical resistant gloves, apron and goggles/face mask to protect from splashes. Avoid contact with skin and eyes. Do not breathe product spray or mist. Ensure adequate exhaust ventilation when in use.
	Measures to prevent fire:	Keep away from sources of ignition - no smoking. Take measures to prevent the build-up of electrostatic charge.
	Advice on general occupational hygiene:	Wash thoroughly after handling.
7.2	Conditions for safe storage, including any incompatibilities: Technical measures and storage conditions:	Store in a cool dry area away from heat and sources of ignition. Keep containers tightly closed when not in use.
	Packaging materials:	Store in original container.
	Requirements for storage rooms and vessels:	Recommended storage temperature 10 °C to 30 °C. Keep containers out of direct sunlight.
	Further information on storage conditions:	Rotate stock and check regularly for damaged items.
7.3	Specific end use(s): Recommendations:	Use only for Non Destructive Testing (NDT) applications.
	Industrial sector specific solutions:	See product data sheet for further information.

SAFETY DATA SHEET

SECTION 8

EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters:

Occupational exposure limit values:

Occupational exposure figures have been set for some of the components of this preparation based on GESTIS International Limit Values or manufacturers' recommendation.

Ingredient name	Country	Limit value - 8 hours		Limit value - short term	
		ppm	mg /m ³	ppm	mg /m ³
Propan-2-ol	UK	400	999	500	1250
	Germany (AGS)	200	500	400 (1)	1000 (1)
	Sweden	150	350	250 (1)	600 (1)
Acetone	UK	500	1210	1500	3620
	Germany (AGS)	500	1200	1000 (1)	2400(1)
	Sweden	250	600	500(1)	1200(1)
	EU	500	1210		
Talc (respirable dust)	UK		1		
	Germany		2		
	Sweden		1		
Aluminium Hydroxide (respirable dust)	Germany (DFG)		1.5		
Calcium Carbonate (respirable dust)	UK		4		
Calcium Carbonate (inhalable dust)	UK		10		
(1) 15 minutes average value					
Data obtained from GESTIS International Limit Values, EH40, supplier's SDS					

Note: Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.

Derived No Effect Level (DNEL) – Acetone

End User	Exposure Route	Exposure Time	Effects	DNEL
Worker	Inhalation	Long term	Systemic	1210 mg/m ³
Worker	Inhalation	Short term	Local	2420 mg/m ³
Worker	Dermal	Long term	Systemic	186 mg/kg bw/day

Derived No Effect Level (DNEL) –Propan-2-ol

End User	Exposure Route	Exposure Time	Effects	DNEL
Worker	Inhalation	Long term	Systemic	500 mg/m ³
Worker	Dermal	Long term	Systemic	888 mg/kg/day

Derived No Effect Level (DNEL) – Aluminium Hydroxide

End User	Exposure Route	Exposure Time	Effects	DNEL
Worker	Inhalation	Long term	Systemic	10.76 mg/m ³
Worker	Inhalation	Short term	Local	10.76 mg/m ³

Derived No Effect Level (DNEL) – Calcium Carbonate

End User	Exposure Route	Exposure Time	Effects	DNEL
Worker	Inhalation	Long term	Systemic	10 mg/m ³
Worker	Inhalation	Long term	Local	4.26 mg/m ³

Note: The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in accordance with specific guidance within the European REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a government regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American

SAFETY DATA SHEET

Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH.

Predicted No Effect Concentration (PNEC)

	Acetone	Propan-2-ol	Aluminium Hydroxide	Calcium Carbonate
Water - Fresh Water	10.6 mg/l	140.9 mg/l	No hazard identified	No data
Water - Marine Water	1.06 mg/l	140.9 mg/l	No hazard identified	No data
Water - Intermittent release	21 mg/l	140.9 mg/l	No hazard identified	No data
Sediment - Fresh water	30.4 mg/kg dw	552 mg/kg	No data	No data
Sediment - Marine water	3.04 mg/kg dw	552 mg/kg	No data	No data
Soil	33.3 mg/kg dw	28 mg/kg	No data	No data
Sewage Treatment plant	100 mg/l	2251 mg/kg	No hazard identified	100 mg/l

8.2 Exposure controls:

Concentrations of product vapours and mists in the working atmosphere must be kept as low as is reasonably practicable. Exposure should be minimised by the use of appropriate containment, engineering control and ventilation measures. Where this is not possible, personal protective equipment should be worn as indicated below where appropriate.

Appropriate engineering controls:

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limits are not exceeded.
Provide eye wash station.
If ventilation is insufficient suitable respiratory protection must be provided.

Personal protection equipment:

Eye and face protection:

Safety glasses with side-shields conforming to EN166.

Skin protection - hand:

Protective gloves conforming to EN374-3. Use chemical resistant gloves recommended by glove manufacturer as being suitable for isopropyl alcohol, if hand exposure is unavoidable. Protective gloves made of Butyl or Nitrile are suitable although other types may be more suitable in other circumstances. For prolonged exposure, recommended gloves with protective index 6, >480 minutes permeation time according to EN374.

Skin protection – other:

As the product is a preparation, consult the glove manufacturer for exact breakthrough time. Glove manufacturer's directions for use should be observed. Wear impervious, flame retardant antistatic protective clothing. The type of protective equipment must be selected according to the concentration and amount of dangerous substance at the specific workplace.

SAFETY DATA SHEET

Respiratory protection:	Use a respirator with appropriate canister type filter cartridge if spraying in confined or unventilated areas. Respirator Type AX (EN371). For higher level protection use type ABEK-P3 (EU EN 143) respirator cartridges. Use respirators and components tested and approved under CEN standards.
Thermal hazards:	Not applicable.
Environmental exposure controls:	Avoid any release to the environment.

SECTION 9

PHYSICAL & CHEMICAL PROPERTIES

9.1	Information on basic physical and chemical properties:	
	Appearance:	Mobile white liquid
	Odour:	Solvent – alcoholic
	Odour threshold:	No data available
	pH:	Neutral
	Melting point/freezing point:	No data available
	Initial boiling point and boiling range:	75 °C
	Flash point (PMCC):	-6 °C
	Evaporation rate (BuAC = 100):	250
	Flammability (solid, gas) (Limits in air):	No data available
	Upper/lower flammability or explosive limits:	2 – 15% (Vol %)
	Vapour pressure:	138 mm Hg @ 38 °C
	Vapour density (Air = 1):	> 1
	Relative density:	0.88 g/cm ³
	Solubility:	87%
	Partition coefficient: n-octanol/water:	+ 0.05 (Propan-2-ol)
	Auto-ignition temperature:	No data available
	Decomposition temperature:	No data available
	Viscosity (ASTM D445):	< 10 mm ² /s @ 20 °C
	Explosive properties:	No data available
	Oxidising properties:	No data available

Note: properties relate to the bulk product only unless otherwise stated.

9.2	Other information:	No other information
------------	---------------------------	----------------------

SECTION 10

STABILITY & REACTIVITY

10.1	Reactivity:	No data available.
10.2	Chemical stability	Stable under normal conditions of use and applications.
10.3	Possibility of hazardous reactions:	No data available.
10.4	Conditions to avoid:	Keep away from sources of ignition, hot surfaces and direct sunlight.
10.5	Incompatible materials:	Strong oxidizing agents. Acids and alkalis.

SAFETY DATA SHEET

10.6 Hazardous decomposition materials: None under normal conditions of storage and use. Smoke, soot and oxides of carbon on combustion.

SECTION 11 TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects: based on data for component materials.

Acute toxicity - oral: Based on the available data, the classification criteria are not met.

Acute toxicity – dermal: Based on the available data, the classification criteria are not met.

Acute toxicity – inhalation: Based on the available data, the classification criteria are not met.

Skin corrosion/irritation: EUH066: Repeated exposure may cause skin dryness and cracking

Serious eye damage/irritation: Eye Irrit. 2 H319: Causes serious eye irritation

Respiratory sensitisation: Based on the available data, the classification criteria are not met.

Skin sensitisation: Based on the available data, the classification criteria are not met.

Germ cell mutagenicity: Based on the available data, the classification criteria are not met.

Carcinogenicity: Based on the available data, the classification criteria are not met.

Reproductive toxicity: Based on the available data, the classification criteria are not met.

STOT single exposure: STOT SE3 H336: May cause drowsiness or dizziness.

STOT repeated exposure: Route of exposure: Inhalation and oral
Based on the available data, the classification criteria are not met.

Aspiration hazard: Based on the available data, the classification criteria are not met.

Information on likely Routes of Exposure and Potential Health Effects:

Inhalation: Vapour concentrations above the recommended exposure levels are irritating to the eyes and respiratory tract, may cause headaches and dizziness, are anaesthetic and may have other central nervous system effects.

Ingestion: Ingestion may cause irritation of the mouth, throat and digestive tract. Absorption of large amounts may cause systemic effects.

Eye contact: This mixture is classified as an eye irritant.

Skin contact: Frequent or prolonged contact with the product may produce irritation and/or skin dryness and cracking. Product will have a de-fatting effect on the skin.

Toxicity Test Results: based on data for component materials, where available.

Acetone

Acute Toxicity – oral	LD50 (rat)	5800 mg/kg
Acute Toxicity – dermal	LD50 (rabbit)	> 7400 mg/kg
Acute Toxicity – inhalation	LC50 (rat)	76000 mg/l (vapours) 4 hr

SAFETY DATA SHEET

Propan-2-ol

Acute Toxicity – oral	LD50 (rat)	4700 – 5800 mg/kg
Acute Toxicity – dermal	LD50 (rabbit)	13000 mg/kg
Acute Toxicity – inhalation	LC50 (rat)	19000 ppm/8hr

Aluminium Hydroxide

Acute Toxicity – oral	LD50 (rat)	> 2000 mg/kg
Acute Toxicity – inhalation	LC50 (rat)	> 2.3 mg/L (4h)

Calcium Carbonate

Acute Toxicity – oral	LD50 (rat)	> 5000 mg.kg
-----------------------	------------	--------------

Other Information:

No other information

SECTION 12

ECOLOGICAL INFORMATION

Based on data for component materials

12.1 Toxicity:

Acetone

Fish	Onchorhynchus mykiss	LC50	96 hours	5540 mg/l
Aquatic Invertebrates	Daphnia pulex	EC50	48 hours	8800 mg/l
Aquatic Invertebrates	Daphnia magna	EC10	28 days	2212 mg/l
Microorganisms	Activated sludge	EC10	30 mins.	1000 mg/l

Propan-2-ol

Fish	LC50	96h	9640 – 10400 mg/l
Daphnia	EC50	48h	7550 – 13299 mg/l
Algae	IC50	72h	> 1000 mg/l

Calcium Carbonate

Fish	LC50	96h	> 200 mg/l
Daphnia	EC50	46h	> 1000 mg/l
Algae	IC50	72h	> 10000 mg/l

12.2 Persistence and degradability:

Propan-2-ol: readily biodegradable

Acetone: readily biodegradable

12.3 Bioaccumulative potential:

This preparation does not contain any substances expected to be bioaccumulative.

Partition coefficient: n-octanol/water (log Kow):

+0.05 (propan-2-ol)

Bioconcentration factor (BCF):

-0.24 @ 20 °C (acetone)

3 (acetone)

12.4 Mobility in soil:

This product will evaporate into the atmosphere from the surfaces of water and soil.

12.5 Results of PBT and vPvB assessment:

This mixture does not contain any substances that are assessed to be a PBT or vPvB.

12.6 Other adverse effects:

No data available.

SECTION 13

DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Dispose of waste and residues in accordance with local authority requirements. Seek the advice of an approved waste disposal contractor for disposal at a licensed facility in accordance with national legislation.

SAFETY DATA SHEET

Product/packing disposal:	Empty containers may contain residual product and flammable vapours. Keep away from sources of ignition. Do NOT remove labels.
Waste codes/waste designations according to LoW:	14 06 03* other solvents and solvent mixtures.

NOTE: Waste codes are assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use. Waste producers need to assess the actual process used when generating the waste and its contaminants in order to assign the proper waste code(s).

Waste treatment – relevant information:	Dispose of waste and residues in accordance with local authority requirements. Seek the advice of an approved waste disposal contractor for disposal at a licensed facility in accordance with national legislation Do not empty down the drain.
Sewage disposal – relevant information:	
Other disposal recommendations:	Use a licensed waste contractor.

SECTION 14 TRANSPORT INFORMATION

14.1 UN number:	ADR/RID: UN1993 IMDG: UN1993 IATA: UN1993
14.2 UN proper shipping name:	ADR/RID: FLAMMABLE LIQUID, N.O.S (Isopropanol & Acetone mixture) IMDG: FLAMMABLE LIQUID, N.O.S (Isopropanol & Acetone mixture) IATA: FLAMMABLE LIQUID, N.O.S (Isopropanol & Acetone mixture)
14.3 Transport hazard class(es):	ADR/RID: 3 IMDG: 3 IATA: 3
14.4 Packing group:	ADR/RID: II IMDG: II IATA: II
14.5 Environmental hazards:	ADR/RID: No IMDG: Marine Pollutant: No IATA: No
14.6 Special precautions for user:	EMS F-E, S-D Emergency action code -2YE Hazard No (ADR) 33
14.7 Transport in bulk according to Annex II of Marpol 73/78 and the IBC code:	Not applicable

SECTION 15 REGULATORY INFORMATION

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**
EU Regulations:
This data sheet complies with the requirements of Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures.
Safety data sheet as required by EU Regulations 1907/2006 and REACH Annex II Amendment (EU) No. 2015/830.

SAFETY DATA SHEET

Information according to 2013/10/EU and 2008/47/EC amendment of the aerosol directive 75/324/EEC.

Not applicable - this product is not an aerosol.

National regulations (Germany):

Wassergefährdungsklasse (water hazard class):

WGK1 - Low hazard to waters

TechnischeAnleitungLuft (TA-Luft):

Class 5.2.5 Organic Substances, except dusts

15.2 Chemical safety assessment:

No chemical safety assessment has been carried out for this mixture by the supplier.

SECTION 16

OTHER INFORMATION

(i) Indication of changes:

Version 17.1 updated in Section 1.4.

Vertical lines on the left hand side indicate an amendment from the previous version.

(ii) Abbreviations and acronyms:

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road (Accord européen relatif au transport international des marchandises Dangereuses par Route)
CAS No.	Chemical Abstracts Service number
CEN	European Committee for Standardisation
CLP	Classification, Labelling Packaging Regulation; Regulation (EC) No 1272/2008
ECHA	European Chemicals Agency
EC50	Half Maximal Effective Concentration
EC number	EINECS and ELINCS number
EINECS	European Inventory of Existing Commercial Substances
ELINCS	European List of notified Chemical Substances
GHS	Globally Harmonized System
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Lethal Concentration to 50% of a test population
LD50	Lethal Dose to 50% of a test population
MPI	Magnetic Particle Inspection
NDT	Non-Destructive Testing
OEL	Occupational Exposure Limit
PBT	Persistent, Bioaccumulative and Toxic Substance
PMCC	Pensky-Martens closed cup method
PPE	Personal Protection Equipment
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation EC (No) 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail (Reglement International concernant le transport des marchandises Dangereuses par chemin de fer)
SDS	Safety Data Sheet
STOT RE	Specific Target Organ Toxicity, Repeat Exposure
STOT SE	Specific Target Organ Toxicity, Single Exposure
TA-Luft	Technical Instructions on Air Quality Control (Technische Anleitung zur Reinhaltung der Luft)
vPvB	Very Persistent and Very Bioaccumulative
WEL	Workplace Exposure Limit
WGK	German Water Hazard Class (Wassergefährdungsklasse)

SAFETY DATA SHEET

(iii) **Key literature and sources of data:**

- Supplier's safety data sheets for components listed in Section 3.
- European Chemicals Agency, <http://echa.europa.eu/>
- GESTIS International Limit Values Database, http://limitvalue.ifa.dguv.de/Webform_gw.aspx
- Occupational Exposure Limits EH40/2005.
- Commission regulation (EU) 2015/830.
- Control of Substances Hazardous to Health Regulations 2002.
- Hazardous waste regulations 2005.
- Health & Safety at Work Act 1974.
- Regulation (EC) No. 1907/2006 (REACH).
- Regulation (EC) No. 1272/2008 (CLP).

(iv) **Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 (CLP):**

Classification according to Regulation (EC) No 1272/2008	Classification procedure
Flam. Liq. 2 H225	Test method
Eye Irrit. 2 H319	Calculation method
STOT SE3 H336	Calculation method
EUH066	Calculation method

(v) **Hazard statements (number and full text):**

H225: Highly flammable liquid and vapour

H319: Causes serious eye irritation

H336: May cause drowsiness or dizziness

EUH066: Repeated exposure may cause skin dryness or cracking

Hazard Class Category Code (full text):

Eye Irrit. 2: Serious eye damage/eye irritation

Flam. Liq. 2: Flammable liquid

STOT SE3: Specific target organ toxicity - single exposure

Relevant precautionary statements (number and full text):

P210: Keep away from heat/sparks/open flames/hot surfaces – No smoking

P261: Avoid breathing dust/fume/gas/mist/vapours/spray

P280: Wear protective gloves/protective clothing/eye protection/face protection

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P370+P378: IN CASE OF FIRE: Use carbon dioxide, foam, dry chemical, water fog or spray for extinction

P243: Take precautionary measures against static discharge.

P264: Wash thoroughly after handling

P271: Use only outdoors or in a well-ventilated area

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

P337+P313: If eye irritation persists get medical advice/attention

P403+P233: Store in a well ventilated place. Keep container tightly closed

P501: Dispose of contents/container to hazardous waste or special collection point.

(vi) **Training advice:**

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene. Chemical hazard risk assessment. Provide adequate information, instruction and training to operators.

SAFETY DATA SHEET

DISCLAIMER

The information and recommendations contained herein are based upon data believed to be up-to-date and correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information and recommendations contained herein. We accept no responsibility and disclaim all liability for any harmful effects that may be caused by (incorrect) use, handling, purchase, resale, or exposure to our product. Customers and users of our product must comply with all applicable health and safety laws, regulations, and orders. In particular, they are under an obligation to carry out a risk assessment for the particular work places and to take adequate risk management measures in accordance with the national implementation legislation of EU Directives 89/391/EEC and 98/24/EC amended by Directive 2014/27/EU.

Revision summary:	Revision Comments	This SDS is valid from the Revision Date. If you require a SDS for the product manufactured before the revision date please contact us at datasheets@magnaflux.co.uk .	
	Revision Date		01.01.2017
	Version		17.1